

## Outdoor Designer Videoflex® 3000x2000mm



### Specification

Pixel Pitch	2.6mm	3.9mm
Diode	SMD1515	SMD2121
Module Size (mm)	500X62.5	500X62.5
Module Resolution (pixels)	192x24	128x16
Screen Unit Size (mm)	3000x2000	3000x2000
Screen Resolution (pixels)	1152x768	767x512
Color Depth	12~16bit	12~16bit
Pixel Density	884,736	392,704
Refreshing Rate (Hz)	≥3,840	≥3,840
Scan Rate	1/24	1/16
Brightness	1800	1800
Screen Weight (kg)	120	120
Viewing Angle (°)	140	140
Input Voltage (V)	DC24V	DC24V
Max Power Consumption	510W/sqm	510W/sqm
Ave Power Consumption	170W/sqm	170W/sqm
Raising Mechanism	Flightcase with hydrolic lift	Flightcase with hydrolic lift
Working Temperature	-20°C/+50°C (working) -40°C/+60°C (storage)	-20°C/+50°C (working) -40°C/+60°C (storage)
IP Level	IP66	IP66
Humidity	10%~60% (working) 10%~90% (storage)	10%~60% (working) 10%~90% (storage)
Lifetime(hrs)	100,000	100,000
Maintemance	Rear	Rear
Spares	5%	5%